


POWER GUN



HOSE REEL (OPTIONAL)

PROFESSIONAL GUN WITH SWIVEL JOINT

EASY LIFTING

AXA BRASS PUMP WITH DOUBLE WATER SEALS AND COATED CERAMIC PISTON EFFICIENCY 98%

1.450 RPM MOTOR

TOTAL STOP DEVICE

WATER TANK (OPTIONAL)

LARGE WHEELS

SELF PRIMING PUMP



GENERAL FEATURES

- AXA pump with international patent
- High efficiency up to 98%
- Stainless steel plungers with ceramic coating
- Self-priming pump
- Easy pump maintenance
- Dry-run safety and leakage return systems (up to 5 hours)
- Double water seals for high temperature
- Integrated by-pass valve for pressure regulation
- Stainless steel valves
- Water tank (optional)
- Inlet 3/4" F
- Outlet M22 x 1,5
- Adjustable detergent device
- Large pressure gauge with rubber protection (diam. 63 mm)
- Motor 1.450 rpm - electric low speed
- Pressure up to 200 bar with a single phase motor (230 V. 50 Hz.)
- On/Off thermal switch protection
- Total stop device
- Large wheels for easy transportation
- Easy front connection
- Professional use
- CE approved



TECHNICAL FEATURES



| Code | r.p.m | Pressure | | Flow rate | | Voltage V/ph/Hz. | Motor | | Nozzle |
|-----------|-------|----------|-------|-----------|-----|------------------|-------|------|--------|
| | | Bar | PSI | l./h | GPM | | Hp. | Amps | |
| PG100.660 | 1.450 | 30÷120 | 1.450 | 660 | 2.9 | 230/1/50-60 | 3 | 10.4 | 0.50 |
| PG105.720 | 1.450 | 30÷105 | 1.522 | 720 | 3.3 | 230/1/50-60 | 3 | 11.8 | 0.60 |
| PG120.660 | 1.450 | 30÷120 | 1.740 | 660 | 2.9 | 230/1/50-60 | 3 | 12.1 | 0.45 |
| PG130.630 | 1.450 | 30÷130 | 1.885 | 360 | 2.8 | 230/1/50-60 | 3 | 12.8 | 0.40 |
| PG130.660 | 1.450 | 30÷130 | 1.885 | 660 | 2.9 | 230/1/50-60 | 3 | 13.8 | 0.40 |
| PG150.600 | 1.450 | 30÷150 | 2.170 | 600 | 2.6 | 230/1/50-60 | 3 | 13.8 | 0.35 |
| PG200.420 | 1.450 | 30÷200 | 2.900 | 420 | 1.9 | 230/1/50-60 | 3 | 13.8 | 0.20 |
| PG160.900 | 1.450 | 30÷160 | 2.320 | 900 | 4.0 | 400/3/50-60 | 4 | 7.5 | 0.50 |
| PG185.780 | 1.450 | 30÷185 | 2.680 | 780 | 3.0 | 400/3/50-60 | 4 | 7.5 | 0.30 |
| PG200.660 | 1.450 | 30÷200 | 2.900 | 660 | 2.9 | 400/3/50-60 | 4 | 7.5 | 0.35 |
| PG200.900 | 1.450 | 30÷200 | 2.900 | 900 | 4.0 | 400/3/50-60 | 5.5 | 9.4 | 0.45 |

